



## AGT-Gold Sensor Cable

Model No.: AGT-G

### Overview

The PermAlert family of sensor cables are designed to meet the requirements of a wide variety of applications and environments including subfloors, overhead pipes, containment pipe systems, direct burial and foam insulation. All sensor cables are easily spliced and terminated with connectors. The AGT-Gold sensor cable has the flexibility to detect both water-based and hydrocarbon liquids. It is also a chemically resistant cable capable of detecting high corrosive liquids.

### AGT-Gold Sensor Cable & Accessories

Model No.	Part No.	Description	Liquids Detected
AGT-G	8017700	AGT-Gold Sensor Cable	Water-based , acids, bases and hydrocarbons
CAGOLD	8027790	Gold Connectors w/Shrink Tube	NA
TAG	8057661	Cable Tags (100 pack)	NA
CMA	8057920	CMA Cable Mounts (100 pack)	NA

### Features & Benefits

- Fast response time with sensing water-based liquids in seconds
- Quick wicking technology for faster response time
- Hydrocarbon sensing for single solution cable
- High degree of accuracy in detecting any liquids along the length of cable
- Chemically resistant and no exposed metal
- Reusable and low maintenance
- High operating temperature - ideal for extreme environment applications
- Ruggedized coaxial cable construction for long service life
- Easy installation for long continuous cable run
- Customizable length and pre-installed connector options available

## Specifications

### Physical and Mountings

Diameter:	0.32" (8.13 mm)
Minimum Bend Radius:	1.5" (38 mm)
Weight:	47 lbs. / 1,000 ft. (27 kg/300 m)
Operating Temperature:	-40°F to 250°F / (-40°C to 120°C)
Maximum Pull Strength:	50 lbs. (23 kg)
Braid Color:	Black

### Performance - Water

Effective Length	<2,500 ft. (750 m)	<5,000 ft. (1500 m)	<7,500 ft. (2300 m)
Detection Sensitivity	3 ft. (1 m)	3 ft. (1 m)	3 ft. (1 m)
Location Accuracy	± 6 ft. (2 m)	± 12 ft. (4 m)	± 18 ft. (5 m)

### Performance - Hydrocarbon

Effective Length	<2,500 ft. (750 m)	<5,000 ft. (1500 m)	<7,500 ft. (2300 m)
Detection Sensitivity	16 ft. (5 m)	35 ft. (11 m)	53 ft. (16 m)
Location Accuracy	± 6 ft. (2 m)	± 26 ft. (8 m)	± 40 ft. (12 m)

### Regulatory Compliance



The information contained in this document is subject to change without notice. PermAlert, a Division of PERMA-PIPE, Inc., believes the information contained herein to be reliable, but makes no representation as to accuracy or completeness. PermAlert offers a sole and exclusive warranty as is stated in the Standard Terms and Conditions of Sale for these products. In no event will PermAlert be liable for any indirect, incidental or consequential damages.

PermAlert, a division of Perma-Pipe, Inc.  
6410 W. Howard Street, Niles, IL 60714-3302  
+1 847.966.2190  
www.permalert.com

Document No. AGT-Gold DS | Rev. B |  
© 2019 PERMA-PIPE, Inc. | All rights Reserved | Printed in the USA |

**A DIVISION OF PERMA-PIPE, INC.**